

TBN Production Breaking Torque Wrenches

Torque range from 0.2 to 200 N.m

Robust Production tools which reduce the chance of incorrect tightening and are compatible with interchangeable end fittings

Industry Sectors

Maintenance
& Repair



Military

Manufacturing



Military



Aerospace



Electronics



Automotive



Consumer Products

For details on the **TBN 2 & 10**
SMA Connector Kit...
see page 58
or call +44 (0) 1483 894 476

Breaking Mechanism

Incorrect tightening is unlikely



Key Benefits

- These wrenches improve control of the fastening process by reducing the risk of both under and over tightening. This is achieved by Torqueleader's unique breaking mechanism, which gives the operator more time to react once the target torque is reached
- Maximises productivity in restricted space applications through their compact slim line design
- Minimises tool replacement and downtime costs through a long lasting durable design proven by Torqueleader's rigorous lifecycle testing process
- Helps maintain production output by minimising operator fatigue through the ergonomic design



TBN Wrenches are preset type torque tools. They must be set to the required value This is done by using a Torque Analyser like the **QTC...** see **page 54** for more details

Models...

TBN 2, 10, 25, 65, 135 & 200

9x12 carrier rectangular fitting version also available

Want to know how to use this tool?



Watch our video



Details of End Fittings... see pages 62 & 64 or visit www.torqueleader.com



Order now... call our Sales Hotline +44 (0) 1483 894 476

Order Code	Model	Range		Drive	k mm	kg	Repeatability	ISO 6789 Class	
		ISO	Imperial						
011100	TBN 2	0.2-2 N.m	1.8-18 lbf.in	Captive Pin	105	0.11	+/- 6%	2C	✓
011110	TBN 2 G	0.2-2 N.m	1.8-18lbf.in		133	0.13	+/- 6%	2C	✓
011200	TBN 10	1-10 N.m	9-89 lbf.in	Captive Pin	105	0.13	+/- 6%	2C	✓
011210	TBN 10 G	1-10 N.m	9-89 lbf.in		133	0.15	+/- 6%	2C	✓
050000	TBN 25	5-25 N.m	4-18 lbf.ft		265	0.41	+/- 4%	2C	✗
050010	TBN 25 G	5-25 N.m	4-18 lbf.ft		265	0.41	+/- 4%	2C	✗
050100	TBN 65	10-65 N.m	7-48 lbf.ft		302	0.75	+/- 4%	2C	✗
050110	TBN 65 G	10-65 N.m	7-48 lbf.ft		302	0.75	+/- 4%	2C	✗
050200	TBN 135	20-135 N.m	15-100 lbf.ft		408	1.03	+/- 4%	2C	✗
050210	TBN 135 G	20-135 N.m	15-100 lbf.ft		408	1.03	+/- 4%	2C	✗
050300	TBN 200	40-200 N.m	29-147 lbf.ft		520	1.40	+/- 4%	2C	✗
050310	TBN 200 G	40-200 N.m	29-147 lbf.ft		520	1.40	+/- 4%	2C	✗